

tasker®

...a project further...

NEW

Armored Cables for Fixed/Underground installation - Anti-Rodents

** Production on demand

| | | ** T21 AR | ** T22 AR | ** T23 AR |
|-----------------------|--------------|--|--------------------------------------|--------------------------------------|
| APPLICATION: | | Loudspeaker Cable | | |
| INNER CABLE | n° Cond. | 2 | 2 | 2 |
| NOMINAL SECTION | AWG | CU 2x16 | CU 2x14 | CU 2x13 |
| CONDUCTOR FORMATION | ø mm | 28x0,25 OFC | 44x0,25 OFC | 54x0,25 OFC |
| INSULATION | ø mm | PVC 3,0 | PVC 3,4 | PVC 3,9 |
| SHEATH | type ø mm | PVC Flame Retardant 7,40 FirestoP | PVC Flame Retardant 8,20 FirestoP | PVC Flame Retardant 8,50 FirestoP |
| SHEATH COLOUR | | Black | Black | Black |
| ARMOR | | Galvanized Steel | Galvanized Steel | Galvanized Steel |
| EXTERNAL CABLE DIAM. | ø mm | 8,40 | 9,20 | 9,50 |
| PACKAGING | m | 100/300/500 | 100/300/500 | 100/300/500 |
| CONDUCTOR RESISTANCE | Ω/Km±5% | 16 | 12 | 9 |
| MAX RATED VOLTAGE | V. | 49 | 49 | 49 |
| OPERATIVE TEMPERATURE | °C | -15/+70 | -15/+70 | -15/+70 |
| Standards: | | RoHS2 2011/65/UE - 2002/95/EC CEI 20/37 and CEI 20-22/II° | | |



Products description

Nuova gamma di cavi armati super resistenti per applicazioni interrate, adatti a pose fisse anche in presenza di roditori.

- Cavi Cassa
- Cavi Microfonici Bilanciati
- Cavi Audio Digitali anche per protocollo DMX
- Cavi Video

Questa linea di prodotti è realizzabile, su richiesta, su bobine di diversa pezzatura. Tutta la gamma è realizzata anche nelle versioni non armate, con guaine in PVC, L.S.Z.H., PE e PUR.

New range of high resistant armored cable for underground installation, for fixed application, even in presence of rodents.

- Loudspeaker Cable
- Balanced Microphone Cable
- Digital Audio Cable also for DMX application
- Video Cable

This products line is available on demand in different size of reels. All these cables are also available in unarmored version with PVC, L.S.Z.H., PE e PUR sheaths.

tasker®

...a project further...

NEW

Armored Cables for Fixed/Underground installation - Anti-Rodents

** Production on demand

| | | ** C114 AR | ** C128 AR | ** TSK1038 AR | ** RG59 AR | ** TSK1078 AR |
|-----------------------|-------------------|--|--------------------------------------|--------------------------------------|--------------------|-----------------------------------|
| APPLICATION: | | Analogue Audio Cable | | Digital Audio Cable | | Digital Video Cable |
| INNER CABLE | n° Cond. | 2 | 2 | 2 | 1 | 1 |
| NOMINAL SECTION | mm² | 1CU 2x0,25 | 1CU+1CS 2x0,35 | CS 2x0,35 | CW 1x0,26 (75Ω) | CU 1x0,52 (75Ω) |
| CONDUCTOR FORMATION | ø mm | 8x0,20 OFC | 11x0,20 OFC | 11x0,20 OFC | 1x0,58 | 1x0,81 |
| INSULATION | ø mm | Compact PE 1,5 | Compact PE 1,7 | PPE 1,6 | Compact PE 3,7 | Foam PE 3,7 |
| SHIELD | type and coverage | Spiral CS 100% | CS Braid 90% | CS Braid 85% | CU Braid 98% | Foil Tape 100% CS Braid 95% |
| SHEATH | type ø mm | PVC Flame Retardant 6,00 FirestoP | PVC Flame Retardant 6,30 FirestoP | PVC Flame Retardant 6,30 FirestoP | PVC 6,10 | LSZH 5,90 FirestoP HalogenFree |
| SHEATH COLOUR | | Black | Black | Black | Black | Black |
| ARMOR | | Galvanized Steel | Galvanized Steel | Galvanized Steel | Galvanized Steel | Galvanized Steel |
| EXTERNAL CABLE DIAM. | ø mm | 7,00 | 7,30 | 7,30 | 7,10 | 6,90 |
| PACKAGING | m | 100/300/500 | 100/300/500 | 100/300/500 | 100/300/500 | 100/300/500 |
| PAIR CAPACITY | pF/m | 55 | 55 | 45 | | |
| CAPACITY core/shield | pF/m | 90 | 92 | 90 | 67 | 53 |
| CONDUCTOR RESISTANCE | Ω/Km±5% | 75 | 60 | 60 | 158 | 33 |
| MAX RATED VOLTAGE | V. | 49 | 49 | 49 | 2000 | |
| IMPEDANCE | Ω±3% | | | | 75 | 75 |
| OPERATIVE TEMPERATURE | °C | -15/+70 | -15/+70 | -15/+70 | -15/+70 | -15/+70 |
| Standards: | | RoHS2 2011/65/UE - 2002/95/EC CEI 20/37 and CEI 20-22/II° | | | | |



Products description

Nuova gamma di cavi armati super resistenti per applicazioni interrante, adatti a pose fisse anche in presenza di roditori.

- Cavi Cassa
- Cavi Microfonici Bilanciati
- Cavi Audio Digitali anche per protocollo DMX
- Cavi Video

Questa linea di prodotti è realizzabile, su richiesta, su bobine di diversa pezzatura. Tutta la gamma è realizzata anche nelle versioni non armate, con guaine in PVC, L.S.Z.H., PE e PUR.

New range of high resistant armored cable for underground installation, for fixed application, even in presence of rodents.

- Loudspeaker Cable
- Balanced Microphone Cable
- Digital Audio Cable also for DMX application
- Video Cable

This products line is available on demand in different size of reels. All these cables are also available in unarmored version with PVC, L.S.Z.H., PE e PUR sheaths.



tasker®

trade mark of MILAN S.r.l.
Viale Europa, 74 20090 Cusago (MI) Italy
Tel. +39 02 9039.4556 - 4158 Fax. +39 02 9039.4551

www.tasker.it